


## OT5515

Reducción rosca hembra/macho.



### Especificaciones técnicas



RP X R	BAG	MASTER BOX	CÓDIGO	L MIN	CH
1/8" x 1/4"	10	600	OT5515A14A18000	-	14
1/8" x 3/8"	10	100	OT5515A38A18000	-	17
1/8" x 1/2"	25	100	OT5515A12A18000	-	21
1/4" x 3/8"	10	500	OT5515A38A14000	-	17
1/4" x 1/2"	10	400	OT5515A12A14000	-	21
1/4" x 3/4"	10	200	OT5515A34A14000	-	27
3/8" x 1/2"	10	400	OT5515A12A38000	-	21
3/8" x 3/4"	10	200	OT5515A34A38000	-	27
3/8" x 1"	10	100	OT5515B01A38000	-	34
1/2" x 3/4"	10	250	OT5515A34A12000	-	27
1/2" x 1"1/4	10	60	OT5515B14A12000	-	34
1/2" x 1"1/2	10	50	OT5515B12A12000	-	48
1/2" x 2"	5	30	OT5515C02A12000	-	60
3/4" x 1"	10	150	OT5515B01A34000	-	34
3/4" x 1"1/4	5	70	OT5515B14A34000	-	42
3/4" x 1"1/2	5	50	OT5515B12A34000	-	48
3/4" x 2"	5	30	OT5515C02A34000	-	60
1" x 1/2"	10	150	OT5515A12B01000	-	34
1" x 1"1/4	5	80	OT5515B14B01000	-	42
1" x 1"1/2	5	60	OT5515B12B01000	-	48
1" x 2"	5	30	OT5515C02B01000	-	60
1"1/4 x 1"1/2	5	70	OT5515B12B14000	-	48
1"1/4 x 2"	5	30	OT5515C02B14000	-	60
1"1/2 x 2"	5	40	OT5515C02B12000	-	60
2" x 3"	1	10	OT5515D03C02000	-	95
2"1/2 x 2"	5	20	OT5515C02C12000	-	76
2"1/2 x 3"	1	10	OT5515D03C12000	-	95

## Aplicaciones



DRINKING  
WATER



HEATING



HVAC



GAS



COMPRESSED  
AIR



SOLAR



FIREFIGHTING